

# DH-PFS3005-5ET-L

## 5-Port Unmanaged Ethernet Switch



- Supports five 10/100 Mbps adaptive ports.
- Small and light, it is easy to carry and has multiple chips embedded in it.
- Easy to operate.



Robust Design



Plug & Play



Optimized Performance



Easy Installation

### System Overview

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a plastic and fanless design, the device provides a more cost-effective option for customers. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

### Functions

#### Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

#### Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

#### Optimized Performance

All ports can transmit streams at high speeds without delay.

#### Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

### Scene



Home



Shop



Dormitory



Meeting Room

## Specification

### Hardware

Included Power Adapter	Yes
Ethernet Port	5
Ethernet Port Speed	100 Mbps
Description of Function Slots	Port 1–5: 5 × 10/100 Base-T
Power Supply	5 VDC; 1 A
Operating Temperature	0 °C to +45 °C (+32 °F to +113 °F)
Operating Humidity	5%–95% (RH)
Storage Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Storage Humidity	5%–95% (RH)
Power Consumption	Idling: 0.1 W; Full load: 0.5 W

### Performance

MTBF	952.50 years
Switching Capacity	1 Gbit
Packet Forwarding Rate	0.744 Mpps
Packet Buffer Size	768 kbit
MAC Table Size	2K

### General

Statics Protection	Air discharge: 8 kV Contact discharge: 4 kV
Lighting Protection	Common mode: 2 kV
Net Weight	0.12 kg (0.26 lb)
Gross Weight	0.23 kg (0.51 lb)
Product Dimensions	86.4 mm × 52.0 mm × 23.0 mm (3.40" × 2.05" × 0.91")
Packaging Dimensions	94.0 mm × 111.0 mm × 67.0 mm (3.70" × 4.37" × 2.64")
Casing Material	Plastic
Installation	Desktop mount
Certifications	CE; FCC

## Dimensions (mm[inch])

